

RUJUKAN SEBUTHARGA : MINDEF/DFA/FY2026/GCAU/TU/LP/1034 NAMA SYARIKAT : _____
 TARIKH TUTUP SEBUT HARGA : 15/06/2026 (KHAMIS, 8:00 PAGI) COP SYARIKAT & TANDATANGAN : _____
 PETI PENERIMAAN SEBUT HARGA : (3) TEL PEMBEKAL : _____ FAX PEMBEKAL : _____
 ALAMAT PETI SEBUT HARGA : ARAS BAWAH, BANGUNAN ARKIB, KEMENTERIAN PERTAHANAN, EMAIL PEMBEKAL : _____
 BOLKIAH GARRISON BB3510 TAFIS VENDOR ID : _____

BIL	KETERANGAN BARANG	KTI	HARGA SATU	HARGA SEMUA	TEMPOH SAH HARGA (MINIMUM 180 HARI)	TEMPOH PENGHANTARAN	BUATAN NEGERI	LAIN-LAIN HAL
	<u>PEMBELIAN P.O.L.A PESAWAT C295MW TUD8</u>							
1	SYNTHETIC TURBINE ENGINE OIL (1QT) PART NO: TURBONYCOIL 160	04 CANS						
2	SOLID FILM LUBRICANT (12OZ) PART NO: PERMA-SLIK GLF	04 CANS						
3	SYNTHETIC LITHIUM COMPLEX GREASE (3KG) PART NO: AEROSHELL GREASE 33	1 CAN						
4	BLUE VARNISH, PAINT ELECTRICAL BONDING PART NO: 4125/6407 + 0613/9000 + 0580/9000 COATING 4125 - 4 LTR ACTIVATOR 0613 - 2 LTR THINNER 0580 - 5 LTR	1 SET						
5	PRESERVATIVE LUBRICATING OIL & CORROSION PREVENTIVE COMPOUND (1 GAL) PART NO: TECTYL 900	04 CANS						
6	GREASE (1KG) PART NO: NYCOREASE GN GA 47	1 CAN						
7	RUBBER PROTECTIVE AGENT (1QT) PART NO: AGE MASTER NO. 1	04 CANS						
8	CORROSION INHIBITING COMPOUND (400ML) PART NO: ARDROX AV 8 (AEROSOL SPRAY CAN)	02 CANS						

MINDEF/DFA/FY2026/GCAU/TU/LP/1034

9	ANTI FRICTION COATING (500G) PART NO: MOLYKOTE 3400A	02 CANS					
10	GREASE (1LB) PART NO: BRAYCOTE 806	02 CANS					
11	TEEPOL-MULTIPURPOSE DETERGENT (5L) PART NO: P0210242	02 BOTTLES					
12	MOULD RELEASE AGENT (750G) PART NO: RENLEASE QZ5111	01 BOTTLE					
13	DYE (58G) PART NO: ORASOL YELLOW081	01 CONTAINER					
14	DYE (35G) PART NO: ORASOL BLUE 825	01 CONTAINER					
15	DYE (44G) PART NO: ORASOL RED365	01 CONTAINER					
16	EPOXY ADHESIVE (98.4ML) PART NO: SW EC-2216 B/A GRAY	04 SETS					
17	SYNTHETIC HYDRAULIC FLUID (1QT) PART NO: HYDRAUNYCOIL FH-42	04 CANS					
18	LITHIUM GREASE (16OZ) PART NO: LUBRIPLATE MO-LITH NO. 2	04 CANS					
19	CORROSION INHIBITING COMPOUND (400ML) PART NO: ARDROX AV 25 (AEROSOL SPRAYCAN)	04 CANS					
20	CORROSION INHIBITING COMPOUND (400ML) PART NO: ARDROX AV 30 (AEROSOL SPRAYCAN)	04 CANS					



21	ANTICORROSIVE COMPOUND (150G) PART NO: MOLYKOTE 111 COMPOUND	04 TUBES									
22	CRC CO CONTACT CLEANER 350GRAM (1 BOTTLE) 12 BOTTLES/BOX PART NO: 2016 PERHATIAN: Perkara-perkara yang perlu (mandatori) dihadapkan sebelum tarikh tutup sebut harga: <table><tr><td>/</td><td>Katalog</td></tr><tr><td>/</td><td>Contoh (Kaunter Utama, Bahagian Perolehan, Aras Bawah, Block D, Jabatanarah Kewangan & Perolehan, Kementerian Pertahanan)</td></tr></table> Jika didapati gagal, sebut harga tersebut tidak akan dipertimbangkan.	/	Katalog	/	Contoh (Kaunter Utama, Bahagian Perolehan, Aras Bawah, Block D, Jabatanarah Kewangan & Perolehan, Kementerian Pertahanan)	01 BOX					
/	Katalog										
/	Contoh (Kaunter Utama, Bahagian Perolehan, Aras Bawah, Block D, Jabatanarah Kewangan & Perolehan, Kementerian Pertahanan)										

JUMLAH SEMUA HARGA YANG DITAWARKAN - ANGKA B\$ _____ DAN PERKATAAN : _____.

TERHAD


CERAIAN 'B'

KEPADA: 55 SKN/G/C295MW/12030

BERTARIKH: 26 SYAWAL 1447H

15 APRIL 2026M

SENARAI SPESIFIKASI PETROLEUM, OIL AND LUBRICANTS (P.O.L) BAGI PESAWAT C295MW TUDB

BIL	JENIS BARANG	PART NO / STOCK NO.	KUANTITI DIPOHONKAN	SPESIFIKASI	CONTOH GAMBAR
(a)	(b)	(c)	(d)	(e)	(f)
01	SYNTHETIC TURBINE ENGINE OIL (1QT)	TURBONYCOIL 160	4 CANS	• APPROVED MIL-PRF-7808 M GRADE 3 • IT IS MADE OF NEOPOLYOL ESTERS CONTAINING ADDITIVES TO IMPROVE ITS ANTI-OXIDANT, ANTI-CORROSION AND EXTREME-PRESSURE PROPERTIES • SHELF LIFE: 1,460 DAYS (~4 YEARS)	
02	SOLID FILM LUBRICANT (12OZ)	PERMA-SLIK GLF	4 CANS	• SOLID FILM LUBRICANT, CORROSION INHIBITOR, ROOM TEMPERATURE CURE • IT SHALL CONTAIN NO GRAPHITE, POWDERED METAL OR OZONE DEPLETING SUBSTANCES • SERVICE TEMPERATURE: -55°C TO 120°C • LAYER THICKNESS OF THE COATING: 5-13 µM • SHELF LIFE: ONE YEAR FROM DATE OF SHIPMENT	


B-1
TERHAD



TERHAD

BIL	JENIS BARANG	PART NO / STOCK NO.	KUANTITI DIPOHONKAN	SPESIFIKASI	CONTOH GAMBAR
03	SYNTHETIC LITHIUM COMPLEX GREASE (3KG)	AEROSHELL GREASE 33	1 CAN	• SYNTHETIC OIL BASE GREASE, THICKENED WITH SOAP OF LITHIUM AND EXTREME PRESSURE ADDITIVES, FOR LUBRICATION OF BEARINGS, ACTUATOR SCREWS AND OTHER EQUIPMENT REQUIRING A LUBRICANT WITH HIGH LOAD CAPACITY AND FOR USE WHERE CORROSION PROTECTION AND WATER RESISTANCE IS REQUIRED • SERVICE TEMPERATURE: -73 TO 120°C • COLOUR: BLUE GREEN, SMOOTH • SHELF LIFE OF 6 YEARS FROM THE DATE OF MANUFACTURE • NO RETEST IS REQUIRED	
04	BLUE VARNISH, PAINT ELECTRICAL BONDING <i>Coating 4125 - 4 Ltr</i> <i>Activator 0613 - 2 Ltr</i> <i>Thinner 0580 - 5 Ltr</i>	4125/6407 + 0613/9000 + 0580/9000	1 SET	• TWO-PARTS DIRECT ADHESION VARNISH, FOR IDENTIFICATION PURPOSES IN ELECTRICAL BONDING PROCESS • THIS PRODUCT IS QUALIFIED BY USE ACCORDING TO AIMS04-04-009 THEREFORE IT HAS NOT IPS • 4125/6407: SHELF LIFE 2 YEARS • 0613/9000: SHELF LIFE 2 YEARS • 0580/9000: SHELF LIFE 10 YEARS	
05	PRESERVATIVE LUBRICATING OIL & CORROSION PREVENTIVE COMPOUND (1GAL)	TECTYL 900	4 CANS	• LOW-VISCOSITY, WATER-DISPLACING, SOLVENT-FREE CORROSION PREVENTIVE COMPOUND DESIGNED TO PROTECT FERROUS AND NON-FERROUS METALS DURING STORAGE AND TRANSIT • SHELF LIFE: 36 MONTHS / 730 DAYS (UNOPENED CONTAINERS)	

TERHAD

BIL	JENIS BARANG	PART NO / STOCK NO.	KUANTITI DIPOHONKAN	SPEKIFIKASI	CONTOH GAMBAR
06	GREASE (1KG)	NYCOGREASE GN GA 47	1 CAN	• ANTI-SEIZE, ASSEMBLY, DISMANTLING COMPOUND • HEAVY LOAD APPLICATIONS (WHEELS, ETC.) • HIGH TEMPERATURE APPLICATIONS (ENGINE SPARK PLUGS, PROPELLER SHAFTS, SPLINES, THREADED FASTENERS, FITTING OF REAR PARTS OF GAS TURBINES, ETC.) • SHELF LIFE: UP TO 72 MONTHS (6 YEARS) ACCORDING TO STANAG 3149 REGULATIONS	
07	RUBBER PROTECTIVE AGENT (1QT)	AGE MASTER NO.1	4 CANS	• APPLY 6 MONTHS AFTER NEW DE-ICER IS INSTALLED • REAPPLY EVERY 150 FLIGHT HOURS (TWICE YEARLY) • ONE QUART COVERS APPROXIMATELY 90 SQ. FT (8.3 SQ. M) • FOR USE ON NEOPRENE DE-ICERS ONLY • ALLOW FOR 24-HOUR DRY TIME • REFER TO ATA 30-10-31, SECTION LLL FOR INSTRUCTIONS • SHELF LIFE: UNLIMITED WHEN STORED CORRECTLY IN ITS ORIGINAL	
08	CORROSION INHIBITING COMPOUND (400ML)	ARDROX AV 8 (AEROSOL SPRAY CAN)	2 CANS	• SUPER-PENETRATING, WATER-DISPLACING CORROSION-INHIBITING COMPOUND (CIC) • IT LEAVES A FIRM, TACK-FREE, LIGHT-BROWN FILM, TYPICALLY APPLIED ON METAL TO PROTECT AGAINST RUST WITH A DRYING TIME OF APPROXIMATELY 60 MINUTES • SHELF LIFE: 36-MONTH	


TERHAD

BIL	JENIS BARANG	PART NO / STOCK NO.	KUANTITI DIPOHONKAN	SPESIFIKASI	CONTOH GAMBAR
09	ANTI FRICTION COATING (500G)	MOLYKOTE 3400A	2 CANS	- HIGH-PERFORMANCE, HEAT-CURED, DARK GREY ANTI-FRICTION COATING DESIGNED FOR METAL-TO-METAL COMBINATIONS INVOLVING HIGH LOADS AND SLOW TO MEDIUM-FAST SPEEDS - DARK GREY, SOLID LUBRICANT (MOLYBDENUM DISULFIDE AND ANTIMONY TRIOXIDE) IN AN ORGANIC BINDER/SOLVENT - SHELF LIFE: 24 MONTHS (UNOPENED)	
10	GREASE (1LB)	BRAYCOTE 806	2 CANS	- NLGI #2 OFF-WHITE, PERFLUOROETHER-BASED GREASE SPECIALIZED FOR EXTREME AEROSPACE AND INDUSTRIAL ENVIRONMENTS -30°C TO 204°C OPERATING RANGE, NONFLAMMABILITY, AND HIGH-VACUUM STABILITY - SHELF LIFE: APPROXIMATELY 3650 DAYS (10 YEARS) FROM DATE OF MANUFACTURE	
11	TEEPOL-MULTIPURPOSE DETERGENT (5L)	P0210242	2 BOTTLES	- GENERAL CLEANING, MANUAL DISHWASHING, AND DEGREASING - GREEN-COLORED LIQUID - SUITABLE FOR ALL WASHABLE SURFACES - SAFE ON MOST SURFACES, INCLUDING PLASTIC WORK SURFACES	

TERHAD

BIL	JENIS BARANG	PART NO / STOCK NO.	KUANTITI DIPOHONKAN	SPESIFIKASI	CONTOH GAMBAR
12	MOULD RELEASE AGENT (750G)	RENLEASE QZ5111	1 BOTTLE	• LIQUID SUSPENSION OF WAXES IN SOLVENT FOR THE RELEASE OF GENERAL AND INTRICATE MOULD SURFACES • LOW VISCOSITY WHITE LIQUID • 12 MONTHS (UNOPENED)	
13	DYE (58G)	ORASOL YELLOW081	1 CONTAINER	• GREENISH-SHADE YELLOW, 1:1 CHROMIUM METAL-COMPLEX SOLVENT DYE FROM SUN CHEMICAL • EXCELLENT SOLUBILITY IN POLAR SOLVENTS (KETONES, ALCOHOLS) AND SUPERIOR LIGHTFASTNESS, MAKING IT IDEAL FOR COLORING EPOXY RESINS • 2-5 YEARS (UNOPENED)	
14	DYE (35G)	ORASOL BLUE 825	1 CONTAINER	• HIGH-PERFORMANCE, TRANSPARENT GREENISH-BLUE COPPER-PHTHALOCYANINE SOLVENT DYE, OFFERING EXCELLENT BLEEDING RESISTANCE AND HIGH COLOR STRENGTH • SHELF LIFE: 6 MONTHS TO 2 YEARS	


TERHAD

BIL	JENIS BARANG	PART NO / STOCK NO.	KUANTITI DIPOHONKAN	SPEKIFIKASI	CONTOH GAMBAR
15	DYE (44G)	ORASOL RED365	1 CONTAINER	- METAL-COMPLEX SOLVENT DYE (SOLVENT RED 160) PRIMARILY USED FOR COLORING SOLVENT-BASED INKS, COATINGS, AND EPOXIES LIKE HXTAL - SHELF LIFE: 5 YEARS OR MORE	
16	EPOXY ADHESIVE (98.4ML)	SW EC-2216 B/A GRAY	4 SETS	- FLEXIBLE, TWO-PART STRUCTURAL EPOXY ADHESIVE (LIQUID/PASTE) DESIGNED FOR HIGH-PERFORMANCE BONDING OF METALS, PLASTICS, AND RUBBERS ~7 DAYS AT ROOM TEMPERATURE, OR 30 MINS AT 93 DEGREE CELSIUS - SHELF LIFE: MINIMUM 12 MONTHS IN UNOPENED, ORIGINAL PACKAGING	
17	SYNTHETIC HYDRAULIC FLUID (1QT)	HYDRAUNYCOIL FH-42	4 CANS	- HIGH-PERFORMANCE, RED SYNTHETIC HYDRAULIC FLUID BASED ON POLY-ALPHA-OLEFINS (PAO) AND ESTERS - IT OPERATES FROM -54 DEGREE CELSIUS TO +200 DEGREE CELSIUS - SHELF LIFE: 48 MONTHS	

B-6
TERHAD



TERHAD

BIL	JENIS BARANG	PART NO / STOCK NO.	KUANTITI DIPOHONKAN	SPEKIFIKASI	CONTOH GAMBAR
18	LITHIUM GREASE (16OZ)	LUBRIPLATE MO-LITH NO.2	4 CANS	• HIGH-PERFORMANCE, STEEL-GRAY, MOLYBDENUM-LITHIUM GREASE DESIGNED AS A PRIMARY FRICTION BARRIER • CONTAINS MOLY FOR HIGH-PRESSURE AND HIGH-FRICTION APPLICATIONS • SHELF LIFE: 5 – 10 YEARS	
19	CORROSION INHIBITING COMPOUND (400ML)	ARDROX AV 25 (AEROSOL SPRAYCAN)	4 CANS	• ORGANIC CORROSION INHIBITING COMPOUND, FORMING A SOFT, COLOURED AND CLEAR FILM. SPECIAL FOR MOVABLE PARTS, I.E. PULLEYS, CONTROL CABLES, ETC. • FLASH POINT: 38°C MIN. • SOLVENT: ALIPHATIC (5% MAX. AROMATICS) • MIN.PROTECTION TIME IN SALT SPRAY: 100 h MIN. • REMOVABLE WITH CLEANING SOLVENTS • SHELF LIFE: 3 YEARS	
20	CORROSION INHIBITING COMPOUND (400ML)	ARDROX AV 30 (AEROSOL SPRAYCAN)	4 CANS	• ORGANIC CORROSION INHIBITING COMPOUND, PENTRANT AND WATER DISPLACING, FORMING A HARD, COLOURED AND CLEAR FILM • FLASH POINT: 38°C MIN • DENSITY: 0.90 g/cm³ MAX • SOLIDS CONTENT: 44-56% • RECOMMENDED FILM THICKNESS: 30-35 µm • SOLVENT: ALIPHATIC (5% MAX.AROMATICS) • REMOVABLE WITH CLEANING SOLVENTS • SHELF LIFE: 3 YEARS	



TERHAD

BIL	JENIS BARANG	PART NO / STOCK NO.	KUANTITI DIPOHONKAN	SPESIFIKASI	CONTOH GAMBAR
21	ANTICORROSIVE COMPOUND (150G)	MOLYKOTE 111 COMPOUND	4 TUBES	• COMPOSITION: SILICONE OIL WITH AN INORGANIC (SILICA) THICKENER • SERVICE TEMPERATURE: -40°C TO 200°C (-40°F TO 392°F) • CONSISTENCY: NLGI GRADE 3-4 (HEAVY CONSISTENCY) • COLOR: TRANSLUCENT WHITE • APPLICATIONS: IDEAL AS A SEALANT FOR VACUUM/PRESSURE SYSTEMS, DAMPING MEDIUM, AND ANTI-STICK AGENT FOR RUBBER/PLASTIC O-RINGS • SHELF LIFE: 60 MONTHS (5 YEARS)	
22	CRC CO CONTACT CLEANER 350 gram (1 botol) 12 botol / box	2016	1 BOX	• FLASH POINT: <0°C (HIGHLY FLAMMABLE) • APPEARANCE: COLOURLESS LIQUID WITH A MILD ETHEREAL ODOUR • EVAPORATION: FAST, RESIDUE-FREE • SAFETY: PLASTIC SAFE, NON-CORROSIVE, AND NON-STAINING • SHELF LIFE: 5 YEARS	

