

ANNEX A – SPECIFICATION

ITEM 01	120 METERS 48MM 8 STRAND NYLON W/PROTECTED EYE SPLICE
----------------	--



Material	Nylon (Polyamide)	
Nominal Diameter (D)	48mm	
Construction	8-Strand	
Minimum Breaking Load	41 tonnes	
Safe Working Load	6.8 tonnes	
Specific Gravity	1.12 – 1.14	Sinks in water
Melting Point	215°C - 250°C	
Elongation at break	18% - 35%	Excellent Shock Absorption
Strength when wet	Reduced by 10%	
UV Resistance	Good	Maintains strength over prolonged sun exposure
Handling	Excellent	

Rope Size Required : 48mm 8strand
Rope Material : Polyamide (Nylon)
Rope Color : White or Cream
Rope Length : 120meters w/ protected eye splice

16 Units X 120meters of 48mm 8-Strand Nylon w/ protected eye splice

ITEM 02	90 METERS 36MM 3 STRAND NYLON W/PROTECTED EYE SPLICE
----------------	---



Material	Nylon (Polyamide)	
Nominal Diameter (D)	36mm	
Construction	3-Strand	
Minimum Breaking Load	24.9 tonnes	
Safe Working Load	4.98 tonnes	
Specific Gravity	1.12 – 1.14	Sinks in water
Melting Point	215°C - 250°C	
Elongation at break	18% - 35%	Excellent Shock Absorption
Strength when wet	Reduced by 10%	
UV Resistance	Good	Maintains strength over prolonged sun exposure
Handling	Excellent	

Rope Size Required : 36mm 3strand
Rope Material : Polyamide (Nylon)
Rope Color : White or Cream
Rope Length : 90meters w/ protected eye splice

08 Units X 90meters of 36mm 3-Strand Nylon w/ protected eye splice

ITEM 03	70 METERS 36MM 3 STRAND NYLON W/PROTECTED EYE SPLICE
----------------	---



Material	Nylon (Polyamide)	
Nominal Diameter (D)	36mm	
Construction	3-Strand	
Minimum Breaking Load	24.9 tonnes	
Safe Working Load	4.98 tonnes	
Specific Gravity	1.12 – 1.14	Sinks in water
Melting Point	215°C - 250°C	
Elongation at break	18% - 35%	Excellent Shock Absorption
Strength when wet	Reduced by 10%	
UV Resistance	Good	Maintains strength over prolonged sun exposure
Handling	Excellent	

Rope Size Required : 36mm 3strand
Rope Material : Polyamide (Nylon)
Rope Color : White or Cream
Rope Length : 70meters w/ protected eye splice

12 Units X 70meters of 36mm 3-Strand Nylon w/ protected eye splice

ITEM 04	70 METERS 28MM 3 STRAND NYLON W/PROTECTED EYE SPLICE
----------------	---



Material	Nylon (Polyamide)	
Nominal Diameter (D)	28mm	
Construction	3-Strand	
Minimum Breaking Load	15.8 tonnes	
Safe Working Load	2.63 tonnes	
Specific Gravity	1.12 – 1.14	Sinks in water
Melting Point	215°C - 250°C	
Elongation at break	18% - 35%	Excellent Shock Absorption
Strength when wet	Reduced by 10%	
UV Resistance	Good	Maintains strength over prolonged sun exposure
Handling	Excellent	

Rope Size Required : 28mm 3strand
Rope Material : Polyamide (Nylon)
Rope Color : White or Cream
Rope Length : 70meters w/ protected eye splice

12 Units X 70meters of 28mm 3-Strand Nylon w/ protected eye splice

ITEM 05	55 METERS 28MM 3 STRAND NYLON W/PROTECTED EYE SPLICE
----------------	---



Material	Nylon (Polyamide)	
Nominal Diameter (D)	28mm	
Construction	3-Strand	
Minimum Breaking Load	15.8 tonnes	
Safe Working Load	2.63 tonnes	
Specific Gravity	1.12 – 1.14	Sinks in water
Melting Point	215°C - 250°C	
Elongation at break	18% - 35%	Excellent Shock Absorption
Strength when wet	Reduced by 10%	
UV Resistance	Good	Maintains strength over prolonged sun exposure
Handling	Excellent	

Rope Size Required : 28mm 3strand
Rope Material : Polyamide (Nylon)
Rope Color : White or Cream
Rope Length : 55meters w/ protected eye splice

12 Units X 55meters of 28mm 3-Strand Nylon w/ protected eye splice

ITEM 06	35 METERS 28MM 3 STRAND NYLON W/PROTECTED EYE SPLICE
----------------	---



Material	Nylon (Polyamide)	
Nominal Diameter (D)	28mm	
Construction	3-Strand	
Minimum Breaking Load	15.8 tonnes	
Safe Working Load	2.63 tonnes	
Specific Gravity	1.12 – 1.14	Sinks in water
Melting Point	215°C - 250°C	
Elongation at break	18% - 35%	Excellent Shock Absorption
Strength when wet	Reduced by 10%	
UV Resistance	Good	Maintains strength over prolonged sun exposure
Handling	Excellent	

Rope Size Required : 28mm 3strand
Rope Material : Polyamide (Nylon)
Rope Color : White or Cream
Rope Length : 35meters w/ protected eye splice

04 Units X 35meters of 28mm 3-Strand Nylon w/ protected eye splice

ITEM 07	12MM 3 STRAND NYLON (220 METERS PER COIL)
----------------	--



Material	Nylon (Polyamide)	
Nominal Diameter (D)	12mm	
Construction	3-Strand	
Minimum Breaking Load	2.7 tonnes	
Safe Working Load	0.45 tonnes	
Specific Gravity	1.12 – 1.14	Sinks in water
Melting Point	215°C - 250°C	
Elongation at break	18% - 35%	Excellent Shock Absorption
Strength when wet	Reduced by 10%	
UV Resistance	Good	Maintains strength over prolonged sun exposure
Handling	Excellent	

Rope Size Required : 12mm 3strand

Rope Material : Polyamide (Nylon)

Rope Color : White or Cream

Rope Length : 220meters per coil

06 Coils X 12mm 3-Strannd Nylon (220 per coil)

ITEM 08	08MM 3 STRAND NYLON (220 METERS PER COIL)
----------------	--



Material	Nylon (Polyamide)	
Nominal Diameter (D)	08mm	
Construction	3-Strand	
Minimum Breaking Load	1.3 tonnes	
Safe Working Load	0.22 tonnes	
Specific Gravity	1.12 – 1.14	Sinks in water
Melting Point	215°C - 250°C	
Elongation at break	18% - 35%	Excellent Shock Absorption
Strength when wet	Reduced by 10%	
UV Resistance	Good	Maintains strength over prolonged sun exposure
Handling	Excellent	

Rope Size Required : 08mm 3strand

Rope Material : Polyamide (Nylon)

Rope Color : White or Cream

Rope Length : 220meters per coil

06 Coils X 08mm 3-Strannd Nylon (220 per coil)

ITEM 09	06MM 3 STRAND NYLON (220 METERS PER COIL)
----------------	--



Material	Nylon (Polyamide)	
Nominal Diameter (D)	06mm	
Construction	3-Strand	
Minimum Breaking Load	0.8 tonnes	
Safe Working Load	0.13 tonnes	
Specific Gravity	1.12 – 1.14	Sinks in water
Melting Point	215°C - 250°C	
Elongation at break	18% - 35%	Excellent Shock Absorption
Strength when wet	Reduced by 10%	
UV Resistance	Good	Maintains strength over prolonged sun exposure
Handling	Excellent	

Rope Size Required : 06mm 3strand
Rope Material : Polyamide (Nylon)
Rope Color : White or Cream
Rope Length : 220meters per coil

06 Coils X 06mm 3-Strannd Nylon (220 per coil)

TECHNICAL INFORMATION SCHEDULES**SCHEDULE 2: TECHNICAL PROPOSAL**

Tenderers shall set out in this Schedule:

1. **Technical Tender Proposal** in response to the Specifications in **Annex A**, including the technical specifications of the products offered. The Technical Proposal should include:

- Description of the product and its specifications, including the brand and country of manufacture.
- Compliance with Specifications in **Annex A**.
- Proposed delivery period.
- Point of Contact for this Tender / Project.
- Declarations of any Sub-Contractors.

Submission of **Sample/Technical Specification** are **mandatory**, and a list of the samples submitted in this Tender should be attached. Clearly labelled samples shall be submitted to General and Consumable Acquisition Unit, Directorate of Finance and Acquisition, Block D, Ground Floor.

All item/goods offered shall be brand new, genuine, unused and free from defects in material or workmanship at the time of delivery. Should any of the items/goods found to be defective and not in compliance to our technical specification, the supplier will undertake to replace them at their own expense.

SCHEDULE 3: CURRENT AND PREVIOUS JOB EXPERIENCE

Tenderers shall set out in this Schedule:

1. List of **Current and Previous Job Experience** in the recent 3 years in the format below. The Government may contact the reference sites or request the Tenderer to arrange visits to the reference sites for tender assessment purposes. The Government shall treat all the information submitted under this Schedule in strict confidence.

No.	MINDEF PO ID	Project Description and Status	Customer Name & Contact Details	Cost	Project Start Date	Project Delivery Date
	<i>(If Relevant)</i>					

SCHEDULE 4: NOT IN USE

This schedule is not necessary for this tender submission.



SCHEDULE 5: BUSINESS CERTIFICATES AND DOCUMENTS

Tenderers shall set out in this Schedule:

1. **Registration Certificate of Companies and Business Names** issued through the Corporate Registry System in the One Common Portal, Ministry of Finance and Economy (MOFE).
2. **Certificate of Incorporation and Particulars of Directors / Managers (Form X)** under Companies Act, Cap 39 pursuant to Section 143.
(for Tenderers (Sdn Bhd / Bhd) registered under the Companies Act (Chapter 39) only)
3. Updated **Statement of Annual Returns** from the past three years submitted to the Registrar of Companies. *(for Tenderers (Sdn Bhd / Bhd) registered under the Companies Act (Chapter 39) only)*
4. Updated **Certificate of Tax Compliance** from Revenue Division, Ministry of Finance and Economy for the past three years in accordance with the Income Tax Act (Chapter 35).
(for Tenderers (Sdn Bhd / Bhd) registered under the Companies Act (Chapter 39) only)

In the event the Tenderer is not able to obtain their updated Certificate of Tax Compliance pursuant to **paragraph 4** above, the Tenderer shall, as an alternative for the most recent financial year only, the Estimated Chargeable Income Form for on-going tax submissions or a reference letter from an external auditor regarding an on-going tax audit can be considered.

5. List of all **Tenderers' Local Employees** in the format below:

Total Number of Local Employees					
% Local Employees in Company					
No.	Local Employee Name	I.C. No.	Position / Title	Monthly Salary / Wage	Other Employee Benefits

6. List of all **Tenderers' Foreign Employees** in the format below:

Total Number of Foreign Employees					
% Foreign Employees in Company					
No.	Foreign Employee Name	I.C. No.	Position / Title	Monthly Salary / Wage	Other Employee Benefits

7. **Company Registration Certificate with Tabung Amanah Pekerja (TAP)** including the details of Employer Account Number.
8. Updated **List of TAP Contributions to Local Employees**.

SCHEDULE 6: TENDERER'S INTEGRITY DECLARATION

Tenderers shall set out in this Schedule:

1. Completed **Tenderer's Integrity Declaration** in the form as attached.

