

KETERANGAN PEMBELIAN TEMPATAN - JKP KEMENTAH

RUJUKAN SEBUTHARGA : MINDEF/DFA/FY2026/NAU/RPK/LP/1001

TARIKH TUTUP SEBUTHARGA : 13 / 8 / 2026 (KHAMIS, 08:00 PAGI)

PETI PENERIMAAN SEBUTHARGA : BOX (2)

ALAMAT BARU : ARAS BAWAH, BANGUNAN ARKIB,
KEMENTERIAN PERTAHANAN, BOLKIAH GARISSON

NAMA SYARIKAT

COP SYARIKAT & TANDATANGAN

TEL PEMBEKAL

FAX PEMBEKAL

EMAIL PEMBEKAL

TAFIS VENDOR ID

BIL	KETERANGAN BARANG	KTI	HARGA SATU	HARGA SEMUA	TEMPOH SAH HARGA (MINIMUM 180 HARI)	TEMPOH PENGHANTARAN	BUATAN NEGERI	LAIN-LAIN HAL
	PERMOHONAN PEMBELIAN TAYAR SERTA PEMASANGAN BAGI KENDERAAN TOYOTA ARMORED LAND CRUISER VX200 KEPUNYAAN REJIMEN PASUKAN KHAS ANGKATAN BERSENJATA DIRAJA BRUNEI (RPK ABDB)							
01	Tayar Saiz 285/60 18 Bagi Toyota Armored Land Cruiser VX200 BG 7007	05 EA						
02	Tayar Saiz 285/60 18 Bagi Toyota Armored Land Cruiser VX200 BG 9009	05 EA						
	Nota : - Serta Installation, Uninstalation, Aligment dan Chamber - Spesifikasi dan contoh gambar disertakan bagi rujukan							
PERHATIAN: Perkara perkara yang perlu (mandatori) dihadapkan sebelum tarikh tutup sebutharga: ☐ Katalog ☐ Contoh (Sila hadapkan ke kaunter Utama, Bahagian Perolehan, Tingkat Bawah, Blok D, Jabatanarah Kewangan & Perolehan, Kementerian Pertahanan Jika didapati gagal, sebutharga tersebut tidak akan dipertimbangkan.								

Jumlah semua harga yang ditawarkan - angka B\$ _____ dan perkataan : _____

SKOP KERJA BAGI PENGGANTIAN TAYAR TOYOTA ARMORED LAND CRUISER VX 200

Bil	Skop Kerja	Caitian
(a)	(b)	(b)
Penggantian Tayar Toyota Armored Land Cruiser VX 200 BG 7007		
01	1.1 Replacement and installation of Tyre size 285/60 R18. • Old tyres should be removed from the wheel. • Old tyres should be handed back to user for disposal purposes. • New tyres should be installed to the intended vehicle mentioned above; BG 7007	
	1.2 Uninstall and Install of the Run Flat system to the wheel. • Vendor should uninstall the run flat before and after the replacement of the new tyre.	
	1.3 Alignment and Chamber. • After the new tyre has been installed, alignment and chamber should be conducted. • Tyre pressure should be check and the right pressure to be put into the tyres.	



Bil	Skop Kerja	Caitian
(a)	(b)	(b)
Penggantian Tayar Toyota Armored Land Cruiser VX 200 BG 9009		
02	2.1 Replacement and installation of Tyre size 285/60 R18. • Old tyres should be removed from the wheel. • Old tyres should be handed back to user for disposal purposes. • New tyres should be installed to the intended vehicle mentioned above; BG 9009.	
	2.2 Uninstall and Install of the Run Flat system to the wheel. • Vendor should uninstall the run flat before and after the replacement of the new tyre.	
	2.3 Alignment and Chamber. • After the new tyre has been installed, alignment and chamber should be conducted. • Tyre pressure should be check and the right pressure to be put into the tyres.	



SPESIFIKASI TEKNIKAL BAGI TAYAR SAIZ 285/60 R18

Bil (a)	Keterangan (b)	Spesifikasi (c)	Catitan (d)
01	Saiz tayar	285/60/R18	
02	Load Index	116 (maximum load: 1,250 kg per tire)	
03	Speed Rating	Maximum speed: 240 km/h	
04	Type	Summer/ Highway Terrain (SUV)	
05	Technical Features	- Wet Safety. - Dry performance. - Less noise and comfort.	

