

KETERANGAN PEMBELIAN TEMPATAN - JKP KEMENTAH

LAMPIRAN 'A'

RUJUKAN SEBUTHARGA : MINDEF / DFA / FY2026 / ITAU / AF / LP / 007

TARIKH TUTUP SEBUTHARGA : 01 / 10 / 2026 (KHAMIS, 08:00 pagi)

NO. PETI SEBUTHARGA: BOX NO 01

ALAMAT PETI SEBUTHARGA : ARAS BAWAH,
BANGUNAN ARKIB,
KEMENTERIAN PERTAHANAN,
BOLKIAH GARISON, BB3510
NEGARA BRUNEI DARUSSALAM.

NAMA SYARIKAT

:

COP SYARIKAT & TANDANTANGAN

:

TEL PEMBEKAL

:

FAX PEMBEKAL

:

EMAIL PEMBEKAL

:

TAFIS VENDOR ID

:

BIL	KETERANGAN BARANG	KTI	HARGA SATU	HARGA SEMUA	TEMPOH SAH HARGA (MINIMUM 180 HARI)	TEMPOH PENGHANTARAN	BUATAN NEGERI	LAIN-LAIN HAL
	<u>PEMBELIAN PERALATAN TEKNOLOGI MAKLUMAT BAGI KEPERLUAN INFORMATION TECHNOLOGY DEVELOPMENT (ITD)</u>							
1	FREE STANDING CABINET, 424, 800 X 1000 MM C/W ALL ACCESSORIES	3 EA						
2	SMART UPS 5000 VA 230V RACK MOUNTED FOR H145	3 EA						
	Nota: Sila rujuk spesifikasi yang disertakan							

PERHATIAN:

Perkara-perkara yang perlu (mandatori) dihadapkan sebelum tarikh tutup sebutharga:

☒

Katalog

☐

Contoh

Jika didapati gagal, sebutharga tersebut tidak akan dipertimbangkan.

JUMLAH SEMUA HARGA YANG DITAWARKAN - ANGKA B\$ _____ DAN PERKATAAN: _____

42U SERVER RACK

Specification and Requirement

Physical Properties	
Rack Height (U Spaces)	42U
Internal Height	Max.1876 mm
Overall Height, Including Casters	Max. 2014 mm
Overall Height, Excluding Casters	Max.1964 mm
Overall Depth	1000 mm
Overall width	600 mm
Color	Plate Mate (Black, Grey, Dark-grey or white)
Enclosure Frame	SPCC or equivalent
19" EIA Rails	SPCC or equivalent
Roof and Floor Panels	SPCC or equivalent
Door type	Perforated Door with Hexagonal Pattern, Split Rear Door with Hexagonal Pattern (Door Lock and Keys are included for all Doors)
Side Panel Type	Lockable Side Panels-Split
Weight Loading (Static)	1800 Kg
Weight Loading (Dynamic)	1080 Kg
Screws and Nuts	M5 Mounting Screws and Cage nuts are included
16-way PDU (Power Distribution Unit) vertical with Surge Protected	Rack Mount Power Distribution Units with UK 3-pin socket. Extruded aluminium housing, and are finished in black, neon rocker-switch, complete with cover, rear earth-stud, and captive input cable terminated with an IEC14, 3-pin UK plug, or 16A or 32A industrial plugs.
KVM Console & Switch c/w cables and accessories	Included



PDU (Power Distribution Unit)



KVM Console



5KVA SMART UPS

Technical Specification and Requirement

Output	
Output Power Capacity	4000 Watts/ 5KVA
Max Configurable Power	4000 Watts/ 5KVA
Nominal Output Voltage	230 Vac
Output Voltage Note	Configurable for 220:230 or 240 Nominal Output Voltage
Efficiency at full load	96.0%
Output Voltage Distortion	LT 5% at full load
Output Freq	47-53Hz or 50Hz Nominal
Other Output Voltage	220, 240 V ac
Topology	Line Interactive
Waveform Type	Sine Wave
Output Connections	IEC 320 C13, IEC 320 C19, IEC Jumpers
Input	
Nominal Input	230 Vac
Input Freq	50/60 Hz +/- 3 Hz (auto sensing)
Input Connections	Hard wire 3-wires
Input voltage range for main ops.	160-286 Vac
Battery Type	VLRA
Typical recharge time	3 hours
Battery	RBC55
Communication Management	
Interface ports	DB-9, RS-232, SmartSlot
Pre-Installed SmartSlot Card	Inclusive
Control Panel	LED status display : On-line, On -Battery : Replace Battery and Overload Indicators
Audible Alarm	Audible and Visible Alarm : Configurable delays
Physical	
Rack Hight	Max.5U
Net. Weight	Max. 10 Kg
Environment	
Ops Temp	0-40 deg C
Relative Humidity	0-95%
Storage Temp	-15 to 45 deg C
Storage Relative Humidity	0-95%
Storage Elevation	0-15000 Meters
Conformance	
Regulatory Approval	C-tick, CE, EN 50091-1, EN 50091-2, GOST, GS-Mark, VDE
Standard Warranty	2 Years repair or replace
Sustainable Offer Status	
RoHS	Compliant
REACH	REACH: Contains No SVHCs

