

KETERANGAN PEMBELIAN TEMPATAN - JKP KEMENTAH

RUJUKAN SEBUTHARGA : MINDEF/DFA/FY2026/ITAU/MAB/LP/016

TARIKH TUTUP SEBUTHARGA : 5 / 11 / 2026 (KHAMIS, 08:00 PAGI)

PETI PENERIMAAN SEBUTHAR: BOX (01)

ALAMAT BARU: : ARAS BAWAH, BANGUNAN ARKIB
KEMENTERIAN PERTAHANAN, BOLKIAH GARISSON

NAMA SYARIKAT : _____

COP SYARIKAT & TANDATANGAN : _____

TEL PEMBEKAL : _____ FAX PEMBEKAL : _____

EMAIL PEMBEKAL : _____

TAFIS VENDOR ID : _____

BIL	KETERANGAN BARANG	KTI	HARGA SATU	HARGA SEMUA	TEMPOH SAH HARGA (MINIMUM 180 HARI)	TEMPOH PENGHANTARAN	BUATAN NEGERI	LAIN-LAIN HAL (WARRANTY)
	<u>PEMBELIAN SERTA PEMASANGAN CCTV PNEUMATIC MAST BESERTA AKSESORI</u>							
1	4 METERS AUTO PNEUMATIC MAST WITH INSTALLATION	01 set						
2	8 METERS PNEUMATIC MAST	06 SET						
<u>Nota:</u> 1) Sila rujuk spesifikasi & gambar yang di sertakan (ANNEX A) <u>PERHATIAN:</u> Perkara-perkara yang perlu (mandatori) dihadapkan sebelum tarikh tutup sebutharga: ☐ / Katalog (Spesifikasi penuh) ☐ Contoh (Sila hadapkan ke Kaunter Utama, Bhg Perolehan, Tingkat Bawah, Block D, DFA) * Katalog yang dihadapkan hendaklah menggunakan katalog bagi item yang ditawarkan dan bukan menggunakan katalog yang disertakan Jabatan ini. Jika didapati gagal, sebutharga tersebut tidak akan dipertimbangkan.								

15/10 JUMLAH SEMUA HARGA YANG DITAWARKAN - ANGKA B\$ _____ DAN PERKATAAN : _____

Specifications of Telescopic Mast

No	Item Description / Specification	Quantity
1	<u>4M ELECTRIC MAST FOR VEHICLE MOUNTED</u>	1 set
	• Extended height: 4m	
	• Retracted height: 1.4m	
	• Maximum payload: 10 kg	
	• No. Of section: 4	
	• Outer diameter of tubes: 52mm to 90mm	
	• Material of the tube: Aluminum alloy 6063	
	• Surface treatment: Anodizing	
	• Locking function: Included	
	• Working temperature: -30°C to 60°C	
	• Maximum wind speed capacity: 70km/h	
	• Top flange: 150mm, 4 holes of 11mm	
	• Lifting method: Remote control and wire control automatically	
	• Motor: DC24V or DC12V for choice	
	• Accessories: Remote controller, wire control handle, and side mount clamp	



No	Item Description / Specification	Quantity
2	<u>8M PNEUMATIC MAST FOR GROUND MOUNTED</u>	6 sets
	• No. Of section: 5	
	• Material of the tube: Aluminum alloy 6063	
	• Surface treatment: Anodizing	
	• Locking function: Included	
	• Working temperature: -30°C to 60°C	
	• Maximum wind speed capacity: 70km/h	
	• Top flange: 100mm, 4 holes of 9mm	
	• Lifting method: Hand pump up manually	
	• Motor: Without	
	• Accessories: Manual hand pump, tripod, and air hose.	

