

KETERANGAN PEMBELIAN TEMPATAN - JKP KEMANTAN

RUJUKAN SEBUTHARGA : MINDEF/DFA/FY2026/GCAU/AP/LP/2090

TARIKH TUTUP SEBUTHARGA : 29 / 10 / 2026 (KHAMIS, 8.00 PAGI)

PETI PENERIMAAN SEBUTHARGA : BOX (05)

ALAMAT BARU: : ARAS BAWAH, BANGUNAN ARKIB
KEMENTERIAN PERTAHANAN, BOLKIAH GARISSON

NAMA SYARIKAT : _____

COP SYARIKAT & TANDA TANGAN : _____

TEL PEMBEKAL : _____ FAX PEMBEKAL : _____

EMAIL PEMBEKAL : _____

TAFIS VENDOR ID: _____

BIL	KETERANGAN BARANG	KTI	HARGA SATU	HARGA SEMUA	TEMPOH SAH HARGA (MINIMUM 180 HARI)	TEMPOH PENGHANTARAN	BUATAN NEGERI	TEMPOH HAYAT PENYIMPANAN (SHELF LIFE)	LAIN-LAIN HAL
	<u>PEMBELIAN KELENGKAPAN BAGI AKADEMI PERTAHANAN</u>								
1	Dynamic Rope Packaging: 200 Meter Per Roll	2 Rolls							
2	Semi-Static Rope Packaging: 200 Meter Per Roll	2 Rolls							
A	<i>As per specifications included.</i>								
B	Tidak perlu dilampirkan Dokumen Syarikat								
C	<u>PERINGATAN:</u> Tidak di benarkan menggunakan katalog Jabatanarah ini. <u>PERHATIAN:</u> Perkara-perkara yang perlu (mandatori) dihadapkan sebelum tarikh tutup sebutharga: ☐ / Katalog ☐ Contoh Jika didapati gagal, sebutharga tersebut tidak akan dipertimbangkan.								

JUMLAH SEMUA HARGA YANG DITAWARKAN - ANGKA B\$ _____ DAN PERKATAAN : _____

PRODUCT SPECIFICATIONS

1. Dynamic Rope – 10.2 mm (200 m/roll)

- **Type:** Single Dynamic Rope
- **Standard:** EN 892:2012+A3:2023 and UIAA certified, or equivalent
- **Diameter:** 10.2 mm
- **Length:** 200 m per roll
- **Weight:** Approximately 66 g/m
- **Dynamic Elongation:** Maximum 33%
- **Static Elongation:** Maximum 8%
- **Sheath Percentage:** Approximately 33%
- **Impact Force:** Maximum 7.8 kN
- **Number of Falls:** Minimum 7 falls
- **Material:** Polyamide
- **Condition:** New and unused
- **Certification:** Relevant product certification and technical data sheet must be provided

2. Semi-Static Rope – 11 mm (200 m/roll)

- **Type:** Type A Semi-Static/Low-Stretch Kernmantle Rope
- **Standard:** EN 1891:1998 Type A, or equivalent
- **Diameter:** 11.0 mm
- **Length:** 200 m per roll
- **Weight:** Approximately 74 g/m
- **Minimum Breaking Load:** 37.3 kN
- **Minimum Strength with Sewn Termination:** 32.1 kN
- **Static Elongation:** Maximum 2.1%
- **Sheath Percentage:** Approximately 34%
- **Material:** Polyamide
- **Condition:** New and unused
- **Certification:** Relevant product certification and technical data sheet must be provided

